



TA-1404 Adjustable Sector

1425-1535 MHz



The TA-1404 is a vertically polarized adjustable sectoral antenna. The antenna consists of a broadband dipole array enclosed in an aluminum cavity with a UV stabilized ASA radome for superior weatherability. The antenna is at DC ground to aid in lightning protection.

Electrical Specifications

- Frequency Range:** 1425-1535 MHz
- Gain:** 15 dBi @ 60°, 13 dBi @ 90°
12 dBi @ 120°, 10.5 dBi @ 160°
- VSWR:** 1.5:1 max.
- Front to Back Ratio:** 20 dB min. 25 dB typical
- Polarization:** Vertical
- Power Rating:** 250 Watts
- H-Plane Beamwidth:** 60, 90, 120, 160 degrees
- E-Plane Beamwidth:** 16 degrees
- Electrical Downtilt:** 0, 2, 4, 6 degrees
- Cross Pol. Discrimination:** 20 dB min.
- Impedance:** 50 ohms nominal
- Termination:** N female (7/16 optional)

Typical mid band values. (For details , contact factory)
Specifications subject to change without notice


Mechanical Specifications

- Length:** 40 in. (1016 mm)
- Width:** 8 in. (203 mm)
- Depth:** 6 in. (152 mm)
- Weight (incl. Clamps):** 25 lb. (11.4 kg)
- Rated Wind Velocity:** 125 mph (200 km/h)
- Hor. Thrust at rated wind:** 139 lb. (63 kg)
- Mechanical Tilt:** 0 - 15 degrees (optional)
- Mounting (O.D.):** 1.75 - 4.0 in. (44.5 - 102 mm)


Materials

- Radiating Elements:** Irridited aluminum
- Reflector:** Irridited aluminum
- Radome:** Gray UV stabilized ASA
- Clamps:** HDG steel

H-Plane



E-Plane



Rev. 1.0

2002-08-07

500 Van Buren Street
P.O. Box 550
Kemptonville, ON K0G 1J0
Canada



ISO 9001:2000
CGSB Registered
Certificate 961004

T: 613-258-5928
T: 877-ANTENNA
F: 613-258-7418
www.tiltek.com